CHIMEI 奇美實業股份有限公司 CHI MEI CORPORATION

59-1, San Chia, Jen Te, Tainan County, Taiwan TEL: 06-266-3000 FAX: 06-266-9069

Component - Plastics E56070

CHI MEI CORPORATION
59-1 SAN CHIA, JEN TE, TAINAN HSIEN 717 TW

DS-553(+)

Polystyrene/Methacrylate Styrene (PS/MS), "KIBILITE", furnished as sheets

Color	Min Thk (mm)	Flame Class	HWI	HAI	RTI Elec	RTI Imp	RTI Str
NC	1.2	HB	-	-	50	50	50
	1.5	HB	-	-	50	50	50
	2.0-2.2	HB	-	-	50	50	50

Comparative Tracking Index (CTI): -
High-Voltage Arc Tracking Rate (HVTR): -
Dielectric Strength (kV/mm): -
Dimensional Stability (%): -
High Volt, Low Current Arc Resis (D495): -
Volume Resistivity (10^x ohm-cm): -

(+) - Optional prefix or suffix; may be used to denote usage of 0-0.5 percent acid scavengers.

ANSI/UL 94 small-scale test data does not pertain to building materials, furnishings and related contents. ANSI/UL 94 small-scale test data is intended solely for determining the flammability of plastic materials used in the components and parts of end-product devices and appliances, where the acceptability of the combination is determined by UL.

Report Date: 2006-06-27
Last Revised: 2010-06-18

Underwriters Laboratories Inc®

c UL us