

CHIMEI 奇美實業股份有限公司

CHI MEI CORPORATION

59-1, San Chia, Jen Te, Tainan County, Taiwan TEL: 06-266-3000 FAX: 06-266-9069

Component - Plastics

E56070

CHI MEI CORPORATION

59-1 SAN CHIA, JEN TE, TAINAN 717 TW

CM-205 (X)

Polymethyl Methacrylate (PMMA), ""Acryrex"" for pellets or ""Acrypoly"" for sheets", furnished as pellets or sheets

Color	Min Thk (mm)	Flame Class	HWI	HAI	RTI Elec	RTI Imp	RTI Str
ALL	1.5	HB	4	0	95	95	95
	3.0	HB	4	2	95	95	95
NC	8.0	HB	1	2	95	95	95

Comparative Tracking Index (CTI): 1

Dielectric Strength (kV/mm): -

High-Voltage Arc Tracking Rate (HVTR): 0

Dimensional Stability (%): -

Inclined Plane Tracking (IPT): -

Volume Resistivity (10^x ohm-cm): -

High Volt, Low Current Arc Resis (D495): 6

(X) - Optional suffix except suffix "B"; may be used to denote usage of different quantities of lubricant.

ANSI/UL 94 small-scale test data does not pertain to building materials, furnishings and related contents. ANSI/UL 94 small-scale test data is intended solely for determining the flammability of plastic materials used in the components and parts of end-product devices and appliances, where the acceptability of the combination is determined by UL.

Report Date: 1982-06-22
Last Revised: 2013-09-22

© 2013 UL LLC

