



# Component - Plastics

File Number: E56070

CHI MEI CORPORATION

59-1 SAN CHIA

JEN TE

TAINAN, 717 Taiwan



## POLYLAC: PA-797(+)

Acrylonitrile Butadiene Styrene (ABS), pellets

(+) - Indicate 0~0.5% acid scavengers.

Flammability	Value	Test Method
Flame Rating		
1.5 mm, ALL	HB	UL 94
3.0 mm, ALL	HB	UL 94
3.0 mm, ALL	HB40	IEC 60695-11-10, -20
1.5 mm, ALL	HB75	IEC 60695-11-10, -20
Electrical	Value	Test Method
Hot-wire Ignition (HWI)		UL 746A
1.5 mm	PLC 5	
3.0 mm	PLC 4	
High Amp Arc Ignition (HAI)		UL 746A
1.5 mm	PLC 0	
3.0 mm	PLC 0	
Comparative Tracking Index (CTI)	PLC 0	UL 746A
High Voltage Arc Tracking Rate (HVTR)	PLC 0	UL 746A
Arc Resistance	PLC 6	ASTM D495
Thermal	Value	Test Method
RTI Elec		UL 746B
1.5 mm	60.0 °C	
3.0 mm	60.0 °C	
RTI Imp		UL 746B
1.5 mm	60.0 °C	
3.0 mm	60.0 °C	
RTI Str		UL 746B
1.5 mm	60.0 °C	
3.0 mm	60.0 °C	