



Component - Plastics

File Number: E194560

ZHEN JIANG CHI MEI CHEMICAL CO LTD

No.88, Hanqiao Road, Zhenjiang New Area
ZHENJIANG, JIANGSU 212132 China



WONDERLITE: PC-110N(f1)(a), PC-6610(f1)(a)

Polycarbonate (PC), pellets

(a) - Ball pressure temperature is in accordance with IEC 60695-10-2 Method B.

(f1) - Suitable for outdoor use with respect to exposure to Ultraviolet Light, Water Exposure and Immersion in accordance with UL 746C.

Flammability	Value	Test Method
Flame Rating		UL 94
1.5 mm, ALL	V-0	IEC 60695-11-10, -20
3.0 mm, ALL	V-0, 5VA	
Glow Wire Flammability Index		IEC 60695-2-12
1.5 mm	960 °C	
3.0 mm	960 °C	
Glow Wire Ignition Temperature		IEC 60695-2-13
1.5 mm	825 °C	
3.0 mm	850 °C	
Electrical	Value	Test Method
Hot-wire Ignition (HWI)		UL 746A
1.5 mm	PLC 3	
3.0 mm	PLC 3	
High Amp Arc Ignition (HAI)		UL 746A
1.5 mm	PLC 1	
3.0 mm	PLC 1	
Comparative Tracking Index (CTI)	PLC 2	UL 746A
Dielectric Strength	30 kV/mm	ASTM D149
High Voltage Arc Tracking Rate (HVTR)	PLC 2	UL 746A
Volume Resistivity	1.0E+14 ohms-cm	ASTM D257 IEC 60093
Arc Resistance	PLC 6	ASTM D495
Thermal	Value	Test Method
RTI Elec		UL 746B
1.5 mm	130 °C	
3.0 mm	130 °C	
RTI Imp		UL 746B
1.5 mm	115 °C	
3.0 mm	120 °C	
RTI Str		UL 746B
1.5 mm	125 °C	
3.0 mm	130 °C	
Ball Pressure Test (135°C)	Pass	IEC 60695-10-2
Physical	Value	Test Method
Dimensional Change	0.0 %	ASTM D1042 ISO 2796
Outdoor Suitability	f1	UL 746C